

NOTES:

- 1. BOND AND GROUND ACCORDING TO NEC 250.
- 2. METER SOCKET MAY BE CONNECTED TO AN EXTERNAL GROUND ROD, IF REQUIRED BY LOCAL INSPECTION AUTHORITIES.
- 3. WHERE METER IS EXPOSED TO VEHICLE TRAFFIC, CUSTOMER INSTALL PROTECTIVE BUMPER POSTS 36" FROM METER. POST SHALL BE 6" RIGID GALVANIZED STEEL PIPE FILLED WITH CONCRETE AND PAINTED BRIGHT YELLOW.
- 4. CT CABINET TO BE INSTALLED ON EXTERIOR BUILDING WALL. (FOR INDOOR CT CABINET INSTALLATIONS CONTACT SUSSEX REC)
- 5. FOR CUSTOMER/ COMPANY RESPONSIBILITIES SEE COMPANY SPECIFIC SERVICE GUIDE EXHIBIT 19.
- 6. NO CONDUIT SHALL ENTER TOP OF CT CABINET.

SUSSEX RURAL ELECTRIC COOPERATIVE	METERING INSTALLATION OUTDOOR CT CABINET	Service Guide	Rev.
64 County Route 639 Sussex, New Jersey 07461		EXHIBIT 13	1 Date 6/07