



NOTES:

- 1. THIS STRUCTURE IS FOR TEMPORARY SERVICE OF SHORT DURATION ONLY, TYPICALLY 6 MONTHS.
- 2. BASE OF TEMPORARY SERVICE POLE MUST BE A MINIMUM OF 3 FEET FROM FOUNDATION.
- 3. SREC TO RUN SECONDARY CABLE TO HANDHOLE OR TRANSFORMER.
- 4. GROUND FAULT PROTECTION SHALL MEET THE NEC 305.
- 5. ALL WOOD PRODUCTS TO BE PRESSURE TREATED.
- FOR CUSTOMER/ COMPANY RESPONSIBILITIES SEE COMPANY SPECIFIC SERVICE GUIDE EXHIBIT 19.
- 7. METER SOCKET MAY BE CONNECTED TO AN EXTERNAL GROUND ROD IF REQUIRED BY LOCAL INSPECTION AUTHORITIES.
- 8. POLE PLACEMENT TO BE APPROVED BY COMPANY.
- 9. CALL STATE ONE CALL AGENCY 5 DAYS BEFORE CONSTRUCTION.

SUSSEX RURAL ELECTRIC COOPERATIVE

DETAIL "A"



TEMPORARY SERVICE UNDERGROUND INSTALLATION

| Service Guide | Rev. |
|-------------------|------|
| | 1 |
| EXHIBIT 2 | Date |
| —/ ·· · · — · · — | |

6/07